

# DuploCOLL® 19021

Single-sided blue tensilized polypropylene tape with rubber solvent based adhesive

Product construction			
	Name	Colour	Thickness [mm]
Carrier	Polypropylene	blue	approx. 0,055
Adhesive	Rubber solvent adhesive		
			<b>Total thickness:</b> approx. 0,074

## Product advantages

- Good adhesion level on different surfaces
- Removable without residue
- High resistance to breakage

## Main application fields

- Palletizing
- Fixation part for white goods products
- Packaging

Product features		Applicability on	
Initial adhesion	● ● ●	Foam	○ ○ ○
Final adhesion	● ● ●	Rubber	○ ○ ○
Dimensional stability	● ● ●	Fabric	○ ○ ○
Adhesion on even surfaces	● ● ●	Glass/Ceramics	● ● ●
Adhesion on rough surfaces	● ○ ○	Wood	○ ○ ○
Ageing resistance	● ○ ○	High energy plastics: PVC, PC, ABS,...	● ● ●
Weathering resistance	● ● ○	Low energy plastics: PE, PP,...	● ○ ○
Chemical resistance	● ● ●	Metal	● ● ●
Resistance to plasticizers	● ○ ○	Paper/Cardboard	● ● ○
● ● ● very suitable    ● ● ○ suitable    ● ○ ○ suitable with reductions    ○ ○ ○ not suitable			

## Specific technical data\*

Temperature range -20 °C to +60 °C

\* Specific test results, statistically not approved.

# DuploCOLL® 19021

**Single-sided blue tensilized polypropylene tape with rubber solvent based adhesive**

Technical Data		
<b>Peel strength</b>	on steel according to DIN EN 1939, edition 1996, at +23 °C +/- 2°C	4,3 N/25 mm



Application	
<b>Recommended application temperature</b>	18 °C to 35 °C
<b>Application guidelines</b>	<a href="http://www.lohmann-tapes.com">www.lohmann-tapes.com</a>

Storage
Adhesive tapes should be stored at room temperature and normal humidity (50-70 %). The storage stability is 1 year after delivery.

Product presentation					
Converted product	Rolls			Spools	
<b>Width [mm]</b>	15	19	25		
<b>Length [m]</b>	50	50	50		
<b>Max. log width: 1360 mm</b>	Other dimensions, die-cuts and sheets on request.				

For mechanical mounting of this adhesive tape we also offer a wide range of application devices.

## **IMPORTANT NOTE**

The physical characteristics contained in this data sheet represent typical or average values. All application related statements, information and recommendations herein are given to the best of our knowledge and practical experience. Many factors beyond our control and uniquely within buyer's knowledge and control can affect the use and performance of our tape in a particular application. EXCEPT AS EXPRESSIVELY AGREED IN WRITING WE DO NOT TAKE OVER ANY WARRANTY OR LIABILITY FOR THE SUITABILITY OR USABILITY OF OUR TAPES FOR CERTAIN PURPOSES AND APPLICATIONS RESULTING FROM BUYER'S SPECIAL USAGE OF THE TAPES. EXCEPT WHERE PROVIDED BY MANDATORY LEGAL PROVISIONS, WE WILL NOT BE LIABLE FOR ANY DIRECT OR INDIRECT MATERIAL OR IMMATERIAL LOSSES OR DAMAGES ARISING FROM THE USAGE OR APPLICATION OF OUR TAPES. Solely the buyer is responsible for determining the suitability of the specific tape for its use in connection with his method of application. Please consult our Technical Applications Department for specific advice.

Date of issue: December 2017

Lohmann GmbH & Co. KG  
 Irlicher Strasse 55  
 56567 Neuwied  
 Germany  
 Phone: + 49 (0) 26 31 34 - 0  
 Fax: + 49 (0) 26 31 34 - 6661  
 E-mail: [info@lohmann-tapes.com](mailto:info@lohmann-tapes.com)

For further information  
[www.lohmann-tapes.com](http://www.lohmann-tapes.com)

