

# DuploCOLL® 265

Double-sided pressure sensitive adhesive tape coated with a high-performance rubber adhesive

## Product construction

	Name	Colour	Thickness [mm]
Liner	Silicone paper	yellow	approx. 0,070
Adhesive covered side	Synthetic rubber		
Carrier	Special paper	white	approx. 0,120
Adhesive open side	Synthetic rubber		
<b>Total thickness:</b>			approx. 0,190

## Product advantages

- The excellent tack guarantees high initial adhesion. Outstanding adhesion on polymers difficult to bond, like polyethylene, polypropylene and polystyrene
- Good bonding to rubber goods, powder- and standard paints
- The adhesive is water-resistant
- Particularly suitable for smooth and even surfaces

## Main application fields

- Mounting of evaporator plates in refrigerators
- Splicing of coated papers, plastic films and metal foils
- Laminating of leather and textiles
- Self-adhesive bonding of rubber goods (mouldings, profiles)
- Bonding to extruded plastic-profiles

## Product features

## Applicability on

Initial adhesion	● ● ●	Foam	● ● ○
Final adhesion	● ● ●	Rubber	● ● ○
Dimensional stability	● ○ ○	Fabric	● ● ○
Adhesion on even surfaces	● ● ●	Glass/Ceramics	● ● ○
Adhesion on rough surfaces	● ● ○	Wood	● ● ●
Ageing resistance	● ○ ○	High energy plastics: PVC, PC, ABS,...	● ● ●
Weathering resistance	● ● ○	Low energy plastics: PE, PP,...	● ● ●
Chemical resistance	● ○ ○	Metal	● ● ●
Resistance to plasticizers	● ○ ○	Paper/Cardboard	● ● ●

● ● ● very suitable    ● ● ○ suitable    ● ○ ○ suitable with reductions    ○ ○ ○ not suitable

# DuploCOLL® 265


Double-sided pressure sensitive adhesive tape coated with a high-performance rubber adhesive

## Specific technical data\*

Peel strength to polyethylene after 24 h at room-temperature	24 N/25 mm
Peel strength to polypropylene after 24 h at room-temperature	39 N/25 mm
SAFT; 0,5 °C/min; 1 kg	65 °C
Temperature range	-10 °C to +70 °C, temporary +85 °C
Mounting tape of evaporator plates in refrigerators (experience)	-40 °C

\* Specific test results, statistically not approved.

## Technical Data

<b>Dyn. Shear strength</b>	on steel according internal method, at +23 °C +/- 2°C , 10mm/min	80 N/150 mm <sup>2</sup>	
<b>Peel strength</b>	on steel according to DIN EN 1939, edition 1996, at +23 °C +/- 2°C	30 N/25 mm	

## Application

**Recommended application temperature** 18 °C to 35 °C

**Application guidelines** [www.lohmann-tapes.com](http://www.lohmann-tapes.com)

## Storage

Adhesive tapes should be stored at room temperature and normal humidity (50-70 %).  
The storage stability is one year after delivery.

## Product presentation

Converted product	Rolls			Spools		
<b>Width [mm]</b>	>6	>12	>19			
<b>Length [m]</b>	50	50	200			
<b>Max. log width: 1260 mm</b>	Other dimensions, die-cuts and sheets on request.					

For mechanical mounting of this adhesive tape we also offer a wide range of application devices.

# DuploCOLL® 265

**Double-sided pressure sensitive adhesive tape coated with a high-performance rubber adhesive**

## **IMPORTANT NOTE**

The physical characteristics contained in this data sheet represent typical or average values. All application related statements, information and recommendations herein are given to the best of our knowledge and practical experience. Many factors beyond our control and uniquely within buyer's knowledge and control can affect the use and performance of our tape in a particular application. EXCEPT AS EXPRESSIVELY AGREED IN WRITING WE DO NOT TAKE OVER ANY WARRANTY OR LIABILITY FOR THE SUITABILITY OR USABILITY OF OUR TAPES FOR CERTAIN PURPOSES AND APPLICATIONS RESULTING FROM BUYER'S SPECIAL USAGE OF THE TAPES. EXCEPT WHERE PROVIDED BY MANDATORY LEGAL PROVISIONS, WE WILL NOT BE LIABLE FOR ANY DIRECT OR INDIRECT MATERIAL OR IMMATERIAL LOSSES OR DAMAGES ARISING FROM THE USAGE OR APPLICATION OF OUR TAPES. Solely the buyer is responsible for determining the suitability of the specific tape for its use in connection with his method of application. Please consult our Technical Applications Department for specific advice.

Date of issue: March 2021

Lohmann GmbH & Co. KG  
Irlicher Strasse 55  
56567 Neuwied  
Germany  
Phone: + 49 (0) 26 31 34 - 0  
Fax: + 49 (0) 26 31 34 - 6661  
E-mail: [info@lohmann-tapes.com](mailto:info@lohmann-tapes.com)

For further information  
[www.lohmann-tapes.com](http://www.lohmann-tapes.com)

